ORWAK FLEX 5010-E

THE ORWAK FLEX 5010-E is a small but tough baler, that requires little space but offers effective compaction. The unit is sturdy, reliable and easy to operate.

Small footprint



Orwak benefits

MORE PRODUCTIVE USE OF TIME

Less time spent on waste handling, more time for your core activities!

MORE SPACE & ORDER

Our balers rapidly minimizes the space the waste takes up, keeping aisles free and tidy.

LESS COSTS, MORE VALUE

More compaction = less waste volume to transport. Fewer transports required results in lower transportation costs and reduced CO_2 emissions. Sorting at source yields a higher quality of waste material for recycling.



Why Orwak Flex?

- Versatile compaction for many different application areas
- + Hygienic and safe compaction and disposal of mixed or hazardous waste
- + Special solutions for special needs



www.orwak.com



ORWAK FLEX 5010-E

Small but tough

ORWAK FLEX 5010-E IS OPTIMIZED FOR:

PAPER

- + Cardboard
- + Shredded
- + Paper sacks

+ Plastic bags

OTHER METALS

+ Metal straps

OTHER PLASTICS

+ Plastic straps

PLASTIC FOIL

+ Shrink film

TOP LOADING

Feeding material into this top-loading baler is fast and convenient, and the compaction ratio is impressive thanks to high pressure on a small surface.

VERSATILE

The design means that the compactor is versatile and can be used for baling waste products such as cardboard, paper, plastic and even thin wood packaging.

COMPACT DESIGN

Thanks to its compact design, the baler fits where you need it to be and is easy to install in any location.



DIMENSIONS & SPECIFICATIONS

| DIMENSIONS | DIMENSIONS ORWAK FLEX 5010-E | | | | | | |
|--------------------|------------------------------|---------|----------|----------------------------|--|--|--|
| Α | В | с | D | E | | | |
| 2140 mm | 910 mm | 1110 mm | 1820 mm | 1295 mm | | | |
| ENERGY CONSUMPTION | | | | | | | |
| STANDBY MODE | | | MAXIMUMO | MAXIMUM OPERATION ONE HOUR | | | |
| | | | 660 W/H | 660 W/H | | | |

TECHNICAL SPECIFICATIONS

| LOADING APERTURE | CYCLE TIME | PRESS FORCE | BALESIZE | BALE WEIGHT | NOISE LEVEL | PROTECTION CLASS | OPERATING POWER | | | |
|------------------------------|------------|--------------|--|--|-------------|------------------|------------------------------------|--|--|--|
| Width: 700mm Depth: 500mm | 36 secs | 3 ton, 30 kN | Width: 700 mm Depth: 500 mm Height: 700 mm | Cardboard: Up to 60 kg Plastic: Up to 80 kg | 70 db (A) | IP 55 | Single phase 230 V, 50 Hz, 10 A | | | |

We reserve the right to make changes to specifications without prior notice. Bale/bag/bin weights are dependent upon material type.

Kalmec Export AB - Manufacturers Repr. Middle East Polhemsgatan 1 S-392 39 Kalmar SWEDEN Tel: +46-48085900 Fax: +46-48017250 E-mail: hg@kalmec.com

